OPPLE Lighting Lab
欧普照明实验室

PHOTOMETRIC RESULTS

Name:	*OPZS201705098-06002-sidaitongdeng-fang12W-3000K*		
Program:	*Far-C15-G1-Downlight*		
Lum. flux:	*933.00 lm*	**Av. Voltage:**	*219.9857 V*
Efficacy:	*81.27 lm/ W*	**Av. Current:**	*0.09574 A*
Maximum:	*321.695 cd*	**Av. Power:**	*11.474 W*
FluxCone-90:	*497.16 lm*	**Av. Power Factor:**	*0.5448*
FluxCone-120:	*734.76 lm*	**Company:**	*Opple*
Date:	*5/18/2017 5:23:06 PM*	**Operator:**	*SLY*

Protocol

LiTG-class: A41
UTE-class: 1.00 E
IES-class: 47 - 79 - 96 - 100 - 100
TM5-class: BZ4

Divergences in the plane through maximum intensity:	Horizontal	Vertical
One half peak divergence	114.4°	114.4°
Half peak side angle (left)	-56.5°	-56.8°
Half peak side angle (right)	57.9°	57.7°
One tenth peak divergence	161.2°	161.1°
Tenth peak side angle (left)	-79.9°	-80.2°
Tenth peak side angle (right)	81.2°	81.0°

C-planes:	0.0°	15.0°	30.0°	45.0°	60.0°	75.0°	90.0°	105.0°	120.0°	135.0°
	150.0°	165.0°	180.0°	195.0°	210.0°	225.0°	240.0°	255.0°	270.0°	285.0°
	300.0°	315.0°	330.0°	345.0°						

Gamma:	0.0°	1.0°	2.0°	3.0°	4.0°	5.0°	6.0°	7.0°	8.0°	9.0°
	10.0°	11.0°	12.0°	13.0°	14.0°	15.0°	16.0°	17.0°	18.0°	19.0°
	20.0°	21.0°	22.0°	23.0°	24.0°	25.0°	26.0°	27.0°	28.0°	29.0°
	30.0°	31.0°	32.0°	33.0°	34.0°	35.0°	36.0°	37.0°	38.0°	39.0°
	40.0°	41.0°	42.0°	43.0°	44.0°	45.0°	46.0°	47.0°	48.0°	49.0°
	50.0°	51.0°	52.0°	53.0°	54.0°	55.0°	56.0°	57.0°	58.0°	59.0°
	60.0°	61.0°	62.0°	63.0°	64.0°	65.0°	66.0°	67.0°	68.0°	69.0°
	70.0°	71.0°	72.0°	73.0°	74.0°	75.0°	76.0°	77.0°	78.0°	79.0°
	80.0°	81.0°	82.0°	83.0°	84.0°	85.0°	86.0°	87.0°	88.0°	89.0°
	90.0°	91.0°	92.0°	93.0°	94.0°	95.0°	96.0°	97.0°	98.0°	99.0°
	100.0°									

Suzhou. OPPLE Light Co . Ltd .
E-mail: niefenfen@opple.com
Tel. 0512 - 63828888 - 7681

OPPLE Lighting Lab
欧普照明实验室

PHOTOMETRIC RESULTS

Name:	*OPZS201705098-06002-sidaitongdeng-fang12W-3000K*		
Program:	*Far-C15-G1-Downlight*		
Lum. flux:	*933.00 lm*	**Av. Voltage:**	*219.9857 V*
Efficacy:	*81.27 lm/ W*	**Av. Current:**	*0.09574 A*
Maximum:	*321.695 cd*	**Av. Power:**	*11.474 W*
FluxCone-90:	*497.16 lm*	**Av. Power Factor:**	*0.5448*
FluxCone-120:	*734.76 lm*	**Company:**	*Opple*
Date:	*5/18/2017 5:23:06 PM*	**Operator:**	*SLY*

Electrical protocol OPZS201705098-06002-sidaitongdeng-fang12W-3000K / C-Plane measurement

[deg]	U [V]	I [A]	P [W]	PF
0.0	219.9850	0.09576	11.479	0.5449
15.0	219.9850	0.09574	11.472	0.5447
30.0	219.9860	0.09574	11.475	0.5448
45.0	219.9860	0.09574	11.473	0.5448
60.0	219.9860	0.09574	11.473	0.5447
75.0	219.9860	0.09573	11.470	0.5447
90.0	219.9860	0.09574	11.475	0.5448
180.0	219.9850	0.09576	11.479	0.5449
195.0	219.9850	0.09574	11.472	0.5447
210.0	219.9860	0.09574	11.475	0.5448
225.0	219.9860	0.09574	11.473	0.5448
240.0	219.9860	0.09574	11.473	0.5447
255.0	219.9860	0.09573	11.470	0.5447
270.0	219.9860	0.09574	11.475	0.5448

Suzhou. OPPLE Light Co . Ltd .
E-mail: niefenfen@opple.com
Tel. 0512 - 63828888 - 7681

OPPLE Lighting Lab
欧普照明实验室

PHOTOMETRIC RESULTS

Name:	*OPZS201705098-06002-sidaitongdeng-fang12W-3000K*		
Program:	*Far-C15-G1-Downlight*		
Lum. flux:	*933.00 lm*	**Av. Voltage:**	*219.9857 V*
Efficacy:	*81.27 lm/ W*	**Av. Current:**	*0.09574 A*
Maximum:	*321.695 cd*	**Av. Power:**	*11.474 W*
FluxCone-90:	*497.16 lm*	**Av. Power Factor:**	*0.5448*
FluxCone-120:	*734.76 lm*	**Company:**	*Opple*
Date:	*5/18/2017 5:23:06 PM*	**Operator:**	*SLY*

Zonal flux OPZS201705098-06002-sidaitongdeng-fang12W-3000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
0.0	321.5	321.7	321.6	0.00	0.00	0.00	0.00
1.0	321.5	321.7	321.6	0.31	0.31	0.03	0.03
2.0	321.3	321.6	321.5	0.92	1.23	0.10	0.13
3.0	320.9	321.4	321.2	1.54	2.77	0.16	0.30
4.0	320.5	321.2	320.9	2.15	4.92	0.23	0.53
5.0	319.9	320.8	320.4	2.76	7.68	0.30	0.82
6.0	319.2	320.3	319.8	3.36	11.04	0.36	1.18
7.0	318.4	319.7	319.1	3.97	15.01	0.43	1.61
8.0	317.5	318.8	318.3	4.56	19.57	0.49	2.10
9.0	316.6	318.0	317.4	5.15	24.72	0.55	2.65
10.0	315.4	317.1	316.3	5.73	30.45	0.61	3.26
11.0	314.3	316.0	315.2	6.31	36.76	0.68	3.94
12.0	312.8	314.8	313.9	6.88	43.64	0.74	4.68
13.0	311.5	313.6	312.6	7.43	51.08	0.80	5.47
14.0	309.9	312.2	311.1	7.98	59.06	0.86	6.33
15.0	308.4	310.7	309.6	8.52	67.58	0.91	7.24
16.0	306.6	309.1	307.9	9.05	76.63	0.97	8.21
17.0	304.9	307.4	306.2	9.56	86.19	1.02	9.24
18.0	302.9	305.6	304.3	10.07	96.26	1.08	10.32
19.0	300.9	303.7	302.3	10.55	106.81	1.13	11.45
20.0	298.7	301.8	300.3	11.03	117.84	1.18	12.63

Suzhou. OPPLE Light Co . Ltd . Tel. 0512 - 63828888 - 7681
E-mail: niefenfen@opple.com

OPPLE Lighting Lab
欧普照明实验室

Zonal flux OPZS201705098-06002-sidaitongdeng-fang12W-3000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
21.0	296.6	299.6	298.1	11.49	129.33	1.23	13.86
22.0	294.2	297.5	295.9	11.94	141.27	1.28	15.14
23.0	291.8	295.2	293.5	12.37	153.64	1.33	16.47
24.0	289.3	292.7	291.0	12.78	166.42	1.37	17.84
25.0	286.5	290.3	288.4	13.18	179.59	1.41	19.25
26.0	284.1	287.7	285.9	13.56	193.15	1.45	20.70
27.0	281.1	285.1	283.1	13.92	207.07	1.49	22.19
28.0	278.4	282.2	280.3	14.27	221.34	1.53	23.72
29.0	275.2	279.5	277.4	14.59	235.93	1.56	25.29
30.0	272.3	276.6	274.4	14.90	250.83	1.60	26.88
31.0	269.1	273.4	271.3	15.19	266.02	1.63	28.51
32.0	265.8	270.1	268.1	15.45	281.47	1.66	30.17
33.0	262.5	267.2	264.8	15.70	297.17	1.68	31.85
34.0	259.2	263.7	261.6	15.93	313.10	1.71	33.56
35.0	255.5	260.5	258.1	16.14	329.24	1.73	35.29
36.0	252.0	256.8	254.5	16.32	345.56	1.75	37.04
37.0	248.3	253.6	250.9	16.48	362.04	1.77	38.80
38.0	244.5	249.8	247.2	16.63	378.67	1.78	40.59
39.0	240.8	246.2	243.5	16.75	395.42	1.80	42.38
40.0	236.7	242.2	239.5	16.84	412.27	1.81	44.19
41.0	232.6	238.3	235.6	16.92	429.18	1.81	46.00
42.0	228.8	234.5	231.5	16.97	446.15	1.82	47.82
43.0	224.5	230.2	227.4	17.00	463.16	1.82	49.64
44.0	220.3	225.9	223.2	17.01	480.16	1.82	51.46
45.0	216.0	222.1	219.0	17.00	497.16	1.82	53.29
46.0	211.6	217.6	214.7	16.96	514.12	1.82	55.10
47.0	207.2	213.3	210.3	16.90	531.03	1.81	56.92
48.0	202.5	208.7	205.6	16.81	547.84	1.80	58.72
49.0	198.1	204.4	201.1	16.70	564.54	1.79	60.51
50.0	193.4	199.8	196.5	16.58	581.12	1.78	62.29
51.0	188.6	195.1	191.8	16.43	597.55	1.76	64.05
52.0	183.6	190.2	186.9	16.25	613.80	1.74	65.79
53.0	178.5	185.2	182.0	16.05	629.84	1.72	67.51
54.0	173.7	180.7	177.1	15.82	645.67	1.70	69.20
55.0	168.6	175.4	172.1	15.59	661.25	1.67	70.87
56.0	163.6	170.5	167.0	15.32	676.58	1.64	72.52
57.0	158.3	165.3	161.8	15.03	691.61	1.61	74.13
58.0	153.1	160.1	156.6	14.72	706.33	1.58	75.71
59.0	147.5	155.0	151.3	14.39	720.72	1.54	77.25
60.0	142.2	149.5	145.9	14.04	734.76	1.50	78.75

Suzhou. OPPLE Light Co . Ltd .
E-mail: niefenfen@opple.com
Tel. 0512 - 63828888 - 7681

OPPLE Lighting Lab
欧普照明实验室

Zonal flux OPZS201705098-06002-sidaitongdeng-fang12W-3000K / C-Plane measurement

Gamma [°]	Imin [cd/klm]	Imax [cd/klm]	Imean [cd/klm]	Zonal flux [lm]	Sum. zonal flux [lm]	Rel. zonal flux [%]	Sum. rel. zonal flux [%]
61.0	136.8	144.3	140.5	13.67	748.43	1.47	80.22
62.0	131.7	139.2	135.2	13.29	761.72	1.42	81.64
63.0	125.9	133.6	129.7	12.88	774.60	1.38	83.02
64.0	120.5	128.2	124.1	12.45	787.05	1.33	84.36
65.0	114.7	122.4	118.5	12.00	799.06	1.29	85.64
66.0	108.8	116.9	112.8	11.54	810.60	1.24	86.88
67.0	103.6	111.3	107.3	11.07	821.66	1.19	88.07
68.0	97.7	105.4	101.5	10.58	832.24	1.13	89.20
69.0	91.9	99.8	95.9	10.07	842.31	1.08	90.28
70.0	86.1	94.1	90.1	9.55	851.86	1.02	91.30
71.0	80.4	88.2	84.3	9.01	860.88	0.97	92.27
72.0	74.8	82.6	78.6	8.47	869.35	0.91	93.18
73.0	69.0	76.7	72.9	7.92	877.27	0.85	94.03
74.0	63.4	71.4	67.3	7.37	884.64	0.79	94.82
75.0	58.0	65.5	61.7	6.81	891.45	0.73	95.55
76.0	52.2	60.0	56.0	6.25	897.70	0.67	96.22
77.0	46.9	54.3	50.4	5.68	903.37	0.61	96.82
78.0	41.4	48.9	45.1	5.12	908.49	0.55	97.37
79.0	36.6	43.6	40.0	4.57	913.06	0.49	97.86
80.0	31.3	38.5	34.7	4.03	917.09	0.43	98.29
81.0	26.3	33.3	29.7	3.48	920.57	0.37	98.67
82.0	21.6	28.5	24.9	2.96	923.53	0.32	98.99
83.0	17.5	23.8	20.4	2.47	926.00	0.26	99.25
84.0	13.2	19.1	16.1	1.99	927.99	0.21	99.46
85.0	9.6	15.0	12.0	1.53	929.52	0.16	99.63
86.0	6.2	11.2	8.4	1.12	930.64	0.12	99.75
87.0	3.6	7.6	5.3	0.75	931.39	0.08	99.83
88.0	1.7	4.7	3.0	0.46	931.85	0.05	99.88
89.0	0.7	2.4	1.4	0.24	932.09	0.03	99.90
90.0	0.6	1.2	0.8	0.12	932.21	0.01	99.92
91.0	0.6	0.8	0.7	0.08	932.29	0.01	99.92
92.0	0.6	0.9	0.7	0.08	932.37	0.01	99.93
93.0	0.6	0.9	0.7	0.08	932.45	0.01	99.94
94.0	0.6	0.8	0.7	0.08	932.53	0.01	99.95
95.0	0.6	0.8	0.7	0.08	932.61	0.01	99.96
96.0	0.6	0.8	0.7	0.08	932.69	0.01	99.97
97.0	0.6	0.8	0.7	0.08	932.76	0.01	99.97
98.0	0.6	0.8	0.7	0.08	932.84	0.01	99.98
99.0	0.6	0.8	0.7	0.08	932.92	0.01	99.99
100.0	0.6	0.8	0.7	0.08	933.00	0.01	100.00

Suzhou. OPPLE Light Co . Ltd .
Tel. 0512 - 63828888 - 7681
E-mail: niefenfen@opple.com

OPPLE Lighting Lab
欧普照明实验室

PHOTOMETRIC RESULTS

Name:	*OPZS201705098-06002-sidaitongdeng-fang12W-3000K*		
Program:	*Far-C15-G1-Downlight*		
Lum. flux:	*933.00 lm*	**Av. Voltage:**	*219.9857 V*
Efficacy:	*81.27 lm/ W*	**Av. Current:**	*0.09574 A*
Maximum:	*321.695 cd*	**Av. Power:**	*11.474 W*
FluxCone-90:	*497.16 lm*	**Av. Power Factor:**	*0.5448*
FluxCone-120:	*734.76 lm*	**Company:**	*Opple*
Date:	*5/18/2017 5:23:06 PM*	**Operator:**	*SLY*

Polar diagram OPZS201705098-06002-sidaitongdeng-fang12W-3000K / C-Plane measurement



Suzhou. OPPLE Light Co . Ltd .
E-mail: niefenfen@opple.com
Tel. 0512 - 63828888 - 7681

OPPLE Lighting Lab
欧普照明实验室

PHOTOMETRIC RESULTS

Name:	*OPZS201705098-06002-sidaitongdeng-fang12W-3000K*		
Program:	*Far-C15-G1-Downlight*		
Lum. flux:	*933.00 lm*	**Av. Voltage:**	*219.9857 V*
Efficacy:	*81.27 lm/ W*	**Av. Current:**	*0.09574 A*
Maximum:	*321.695 cd*	**Av. Power:**	*11.474 W*
FluxCone-90:	*497.16 lm*	**Av. Power Factor:**	*0.5448*
FluxCone-120:	*734.76 lm*	**Company:**	*Opple*
Date:	*5/18/2017 5:23:06 PM*	**Operator:**	*SLY*

Illuminance and Intensity diagram OPZS201705098-06002-sidaitongdeng-fang12W-3000K / C-Plane measurement



Suzhou. OPPLE Light Co . Ltd .
E-mail: niefenfen@opple.com
Tel. 0512 - 63828888 - 7681

OPPLE Lighting Lab
欧普照明实验室

PHOTOMETRIC RESULTS

Name:	*OPZS201705098-06002-sidaitongdeng-fang12W-3000K*		
Program:	*Far-C15-G1-Downlight*		
Lum. flux:	*933.00 lm*	**Av. Voltage:**	*219.9857 V*
Efficacy:	*81.27 lm/ W*	**Av. Current:**	*0.09574 A*
Maximum:	*321.695 cd*	**Av. Power:**	*11.474 W*
FluxCone-90:	*497.16 lm*	**Av. Power Factor:**	*0.5448*
FluxCone-120:	*734.76 lm*	**Company:**	*Opple*
Date:	*5/18/2017 5:23:06 PM*	**Operator:**	*SLY*

Cartesian diagram OPZS201705098-06002-sidaitongdeng-fang12W-3000K / C-Plane measurement



Suzhou. OPPLE Light Co . Ltd .
E-mail: niefenfen@opple.com
Tel. 0512 - 63828888 - 7681